

ULTIMA RB6.6 SET UP SHEET



Name _____ Date _____ Truck / City _____ Event _____

Front Suspension

Upper Spacer: _____ mm

4.8mm Ball Stud: Camber: _____ °

UM128(Std.) UMW508 (+2mm High Mount)

AL. Steering Support: None UMW724

4.8mm Ball Stud: LA246 (-1mm Low Mount) 97050M (Std)

Ackerman Steer Spacer: _____ mm

UMW701 Aluminum ST Plate UMW702 Aluminum Clank Arm

Toe: In Out _____ °

Tie Rod: _____

4.8mm Ball Stud Spacer: _____ mm

Axle Spacer: Out _____ mm In _____ mm

Wheel Hub: UM569 / Std UM506

Wheelbase: F: _____ mm R: _____ mm

Front Bulkhead Weight Placement:

None Bulkhead Inside _____ oz _____ g On the skid plate _____ oz _____ g * 1oz=28g

Caster: 25° 30° **Caster Block:** 0.5 0° 1.0 2° None 4°

Spacer: A (UM502) B (UMW722/Brass) B (UMW721/Std) B (UMW723/Alu) C (UM567)

Caster Block Position: IN (wide/Std) OUT (Narrow)

Bump Steer Spacer: _____ mm

Axle Height Spacer: _____ mm

Comments: _____

Rear Suspension

Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Anti-Squat: _____ °

4.8mm Ball Stud: UM129 UMW508 (+2mm High Mount) 97050M UM128(Std.)

Upper Spacer: _____ mm

Wheelbase: F: _____ mm R: _____ mm

RR: _____

Mid: _____

Universal Swing Shaft: _____

Camber: _____ °

Drive Hub : 4mm (TFW113) 4.5mm (LAW30GM/Std.) 5.2mm (UMW523)

Wheelbase: F: _____ mm R: _____ mm

Sway Bar: None _____ mm

Rear Hub Carrier : 0° Type-B (UM519) 0° Type-B2 (UM519-2) 0° Alu (UMW704-0) 0.5° Alu (UMW704-05) 1° Alu (UMW704-1)

Lower Sus. Holder: Plastic RF RF2L RF2 Option UMW511GM (RF/Alu)

(Opt/Adjustable) UMW705(RF/Alu) _____ Block UMW725(RF-MID/Bra) _____ Block

(Opt/Adjustable) UMW706(RR-RWD) _____ Block UMW707(RR-MID) _____ Block

Diff.

Gear Diff. # _____ Ball Diff.

Shock

	Front	Rear
Shock Piston:	_____	_____
Shock Oil:	# _____	# _____
Shock Spring:	_____	_____
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	_____ mm	_____ mm
O-ring:	_____	_____
Shock Top type:	<input type="checkbox"/> Alu(UM719/Std) <input type="checkbox"/> UM753-1	
Ball End type:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	

Battery Placement:

None Screw

Front: _____ Rear: _____

Foam: Front Rear None

Transmission

Rear Motor Mid-Ship 3 Gear Mid-Ship 4 Gear Mid-Ship Laydown

Chassis

F _____ mm **Ride Height:** R _____ mm

Battery Type

Straight Separate Short

Type: _____

Truck Condition

Smooth Sandy Bumpy Soft Dirt Low Truction Grass Med. Truction Blue Groore Higt Truction Clay Wet Dusty Dry Other

Wing

Wing Mount : Narrow Wide

Wing Angle : 4° 7° 10°

Blast-S Blast-L Step-S Step-M Step-L Step 2.0 Step 3.0 Straight Round

Lip : _____

Tire

	Front	Rear	Traction Compound or comment:
Tire:	_____	_____	_____
Inserts:	_____	_____	_____
Wheel:	_____	_____	_____

Other

Motor: _____
ESC: _____
Pinion/Spur: _____

Comment
