

Name \_\_\_\_\_ Date \_\_\_\_\_ Track / City \_\_\_\_\_ Event \_\_\_\_\_

### Front Suspension

Upper Spacer: \_\_\_\_\_ mm

4.8mm Ball Stud:  UM128(Std)  UMW508(+2mm High Mount)

Camber: \_\_\_\_\_ °

4.8mm Ball Stud:  LA246 (-1mm Low Mount)  97050M (Std)

Ackerman Steer Spacer: \_\_\_\_\_ mm

Front Tower:  Std  Carbon

Toe:  In  Out \_\_\_\_\_ °

Tie Rod: \_\_\_\_\_

Front Bulkhead Weight Placement:  None  Bulkhead Inside \_\_\_\_\_ oz \_\_\_\_\_ g  On the skid plate \_\_\_\_\_ oz \_\_\_\_\_ g \* 1oz=28g

Caster:  25°  30°

Spacer:  0.5  1.0  None

Caster Block position:  IN (wide/Std)  OUT (Narrow)

Wheel Hub: \_\_\_\_\_ mm

Knuckle:  Std  Carbon

Bump Steer Spacer: \_\_\_\_\_ mm

Front Axle:  UM569 (Std)  UM506 (RB5)

4.8mm Ball Stud Spacer: \_\_\_\_\_ mm

Axle Spacer:  Out \_\_\_\_\_ mm  In \_\_\_\_\_ mm

4.8mm Ball Stud: \_\_\_\_\_ mm

Comments: \_\_\_\_\_

Wheelbase: F: \_\_\_\_\_ mm R: \_\_\_\_\_ mm

### Rear Suspension

Rear Tower:  Std  Carbon

Sus Holder Spacer: F  0.5  1.0  None R  0.5  1.0  None

Anti-Squat: \_\_\_\_\_ °

Upper Spacer: \_\_\_\_\_ mm

Hub spacing: F: \_\_\_\_\_ mm R: \_\_\_\_\_ mm

Outer Bearing:  5X10  5X11  5X13

4.8mm Ball Stud:  UM129  UMW508(+2 High mount)  97050M  UM128(Std)

Sway Bar:  None  \_\_\_\_\_ mm

Camber: \_\_\_\_\_ °

Wheelbase(arm): F: \_\_\_\_\_ mm R: \_\_\_\_\_ mm

Universal Swing Shaft: \_\_\_\_\_

RR: Upper Spacer: \_\_\_\_\_ mm

Lower Sus Holder: Normal  Aluminum(Opt)

Mid:  RF  UMW511+UMW512  RM UMW705/706  RF2  UMW514+UMW515  MM UMW705/707

Motor Position:  Rear Motor  Midship Motor

Diff.:  Gear Diff. # \_\_\_\_\_  Ball Diff.

Comments: \_\_\_\_\_

### Shock

Shock Piston: \_\_\_\_\_

Shock Oil: # \_\_\_\_\_ # \_\_\_\_\_

Shock Spring: \_\_\_\_\_

Limiters: in out mm in out mm mm

Shock Length(A): \_\_\_\_\_ mm \_\_\_\_\_ mm

Shock Length(B): \_\_\_\_\_ mm \_\_\_\_\_ mm

O-ring: \_\_\_\_\_

Ball End type: Front: S  M  L  Rear: S  M  L

Shock Cap:  UM719(Std)  UM753-1(Bleeder)

### Battery Placement:

UM787  None  Screw

Comments: \_\_\_\_\_

Front \_\_\_\_\_ Rear \_\_\_\_\_

Foam:  Front  Rear  None

### Battery Type

Straight  Saddle  Short

Type: \_\_\_\_\_

### Chassis

UM700(Std)  UMW720(Lightweight)

F \_\_\_\_\_ mm Ride Height: R \_\_\_\_\_ mm

### Other

Motor: \_\_\_\_\_

ESC: \_\_\_\_\_

Pinion/Spur: \_\_\_\_\_

### Tire

Front \_\_\_\_\_ Rear \_\_\_\_\_ Traction Compound and/or comments: \_\_\_\_\_

Tire: \_\_\_\_\_

Inserts: \_\_\_\_\_

Wheel: \_\_\_\_\_

### Comments:

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

### Track Condition

Smooth  Sandy  Bumpy  Soft Dirt  Low Bite  Grass  Med. Bite  Blue Groove  High Bite  Clay  Wet  Dusty  Dry  Other

### Body&Wing

UMB03  UMB03LW

Wing Mount:  Narrow  Wide

Wing Angle:  4°  7°  10°

Blast-S  Blast-L  Step-S  Step-M  Step-L  Step 2.0

Lip: \_\_\_\_\_