

Name _____ Date _____ Truck / City _____ Event _____

Front Suspension:

4.8mm Ball Stud:
 UM128 (Std)
 UMW508 (+2mm High Mount)

Upper Spacer: _____ mm

Shock Mount:
 IN
 OUT

Camber: _____ °

4.8mm Ball Stud:
 LA246 (-1mm Low Mount)
 UM129 (Std)

Ackerman Steer Spacer: _____ mm

Bump Steer Spacer: _____ mm

Upper Spacer: _____ mm

Toe: In Out _____ °

Sus Mount:
 UM503
 UM567
 UM721

Caster Spacer:
 25° 0.5
 30° 1.0
 None

Upper Spacer: _____ mm

Axle Spacer:
 Out _____ mm

Axle Height Spacer:
 Up
 Down

Caster Block:
 IN (wide/Std)
 OUT (Narrow) _____ °

Wheelbase: Long Middle Short

Comments: _____

Rear Suspension:

Sus Holder Spacer:
 F 0.5 1.0 None
 R 0.5 1.0 None

Anti-Squat: _____ °

Sway Bar: None _____ mm

Upper Spacer: _____ mm

Wheelbase:
 F: _____ mm
 R: _____ mm

Upper Spacer: _____ mm

MM 1 2

Upper Spacer: _____ mm

Lower Sus Holder:
 Normal Aluminum(Opt)
 RF RF2 Front _____ Rear _____

Upper Spacer: _____ mm

Comments: _____

Drive:
 Rear Motor
 Midship Motor

Diff:
 Gear Diff. # _____
 Ball Diff. _____

Shock:

	Front		Rear	
Shock Piston:	_____	_____	_____	_____
Shock Oil:	# _____	# _____	# _____	# _____
Shock Spring:	_____	_____	_____	_____
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	_____ mm	_____ mm	_____ mm	_____ mm
Shock Top Type:	<input type="checkbox"/> Nomal	<input type="checkbox"/> Alu(UM719)		
5.8mm Ball End:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L		

Chassis:

Weight Placement:

F _____ mm Ride Height: R _____ mm

Tire: Front _____ Rear _____

Inserts: _____

Wheel: _____

Traction Compound: _____

Comment : _____

Battery Placement:

Front _____ Rear _____

Electronics:

Motor: _____

Pinion/Spur: _____

Battery: _____

ESC: _____

Radio: _____

Servo: _____

Throttle/Brake: _____

EPA: _____ **Expo:** _____

Initial brake: _____

Drag brake: _____

Throttle profile: _____

Steering expo: _____

Steering speed: _____

Body:

Material:

- Screw:** Steel Titanium
- Servo Hone:** Nomal Rigid(UM717)
- Pinion Gear:** Steel Aluminium
- Shock Ring:** O-ring X-ring Red Clear