

LAZER ZX7 SETUP SHEET

KYOSHO
THE BEST RACE CONTROL MONITOR

Name: Ryan Van Riper Date: _____ Track / City: Rc Car World. New Jersey Event: Season opener

Front Suspension

Shock Position:

Shock Stay:
 Std.
 Carbon (LAW58)

Lower Sus Holder Block:
 Front B out Rear B out

Lower Sus Holder Spacer:
 Front 1 mm Rear 1 mm

Upper Arm Position:

4.8mm Ball Stud:
 UM129 (Std)
 97050M

Upper Spacer: _____ mm

Camber: 2°

Spacer: 1 mm

Shock Position:

Wheelbase: Front 1 mm Rear 1 mm

Bump Steer Spacer: 0 mm

Toe:
 In
 Out 1°

Sway Bar:
 None
 2 mm

Ackerman Spacer: 3 mm

Axle-Height Spacer:
 Up
 Down

Caster Block:
 7°
 10°
 13°

Sus Bushing:
 Wide
 Narrow (STD)

Carbon front lower brace #KYOLAW71- carbon arm #KYOLAW73

Front Diff

Gear 10k
 Ball _____

Rear Suspension

Shock Position:

Shock Stay:
 Std.
 Carbon (LAW59)

Wing Stay Position

Lower Sus Holder Block:
 Front B in Rear E in

Lower Sus Holder Spacer:
 Front 2.5 mm Rear 2 mm

Upper Arm Position:

4.8mm Ball Stud:
 97050M (Std)
 UM129

Upper Spacer: 0 mm

Toe In: _____

Camber: 2°

Sus. Arm:
 LA272
 UM713B
 UM762(Std)

Hub Carrier:
 0° Type-B (UM519)
 0° Type-B2 (UM519-2)
 0° Alu (UMW704-0)
 0.5° Alu (UMW704-05)
 1° Alu (UMW704-1)

Upper Spacer: 2 mm

Sus Bushing:
 In
 Out (Std)

Wheelbase: Front 2 mm Rear 0 mm

Shock Position:

Wheelbase: Front 1 mm Rear 1 mm

Carbon rear lower brace #KYOLAW72 UMW742- carbon arm UMW742

Center Drive

Diff. Gear Slipper Clutch

Rear Diff.

Gear 10k
 Ball _____

Shocks

	Front	Rear
Piston:	<u>2x1.6</u>	<u>2x1.7</u>
Oil:	<u>600</u>	<u>500</u>
Spring:	<u>Yellow</u>	<u>Red</u>
Limiters:	in _____ mm out <u>19.5</u> mm	in _____ mm out _____ mm
Length (A):	<u>19.5</u> mm	<u>27.5</u> mm
Top Type:	<input type="checkbox"/> Alu. (UM719) <input checked="" type="checkbox"/> UM753-1B (Std)	
Ball End:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input checked="" type="checkbox"/> L Rear: <input type="checkbox"/> S <input checked="" type="checkbox"/> M <input type="checkbox"/> L	Spring Cup Front: <input type="checkbox"/> <input type="checkbox"/> Rear: <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>

Chassis

Centre Bulk:
 Front Rear (Std)

Front: 13 mm
Ride Height: _____ mm
Rear: 13 mm

Electronics

Motor: Trinity xfactor 13.5t
 Pinion/Spur: 26/78
 ESC: HW XR10 Pro Stock
 Radio: Sanwa M12s
 Servo: Protek 160T
 48* timing on motor

Tires

	Front	Rear
Tire:	<u>Jconcepts swaggers</u>	<u>Jconcepts Twin Pins</u>
Compound:	<u>Pink</u>	<u>Pink</u>
Insert:	<u>Stock</u>	<u>Stock</u>
Wheel:	<u>Kyosho</u>	<u>Kyosho</u>

Body & Wing

Body: Stock

Wing Dam Height: _____ mm

Wing: RB7

Wing Angle: 4° 7° 10°

Lip Height: Lowest line mm

Notes

LAW76 Aluminum Center Shaft
LAW78 Aluminum Center Shaft
LAW75 Titanium Screw Set (ZX7)

Track Condition

<input type="checkbox"/> Smooth	<input type="checkbox"/> Sandy
<input type="checkbox"/> Bumpy	<input type="checkbox"/> Soft Dirt
<input type="checkbox"/> Low Traction	<input type="checkbox"/> Grass
<input type="checkbox"/> Med. Traction	<input type="checkbox"/> Blue Groove
<input checked="" type="checkbox"/> High Traction	<input type="checkbox"/> Clay
<input type="checkbox"/> Wet	<input type="checkbox"/> Dusty
<input type="checkbox"/> Dry	<input type="checkbox"/> Carpet

Material

Screw: Steel Titanium

Pinion Gear: Steel Aluminium

Shock O-Ring: O-ring X-ring Red Clear