

Name _____ Date _____ Truck / City _____ Event _____

Front Suspension

Upper Spacer: _____ mm

4.8mm Ball Stud:
 UM128 (Std)
 UMW508 (+2mm High Mount)

Shock Mount:
 IN
 OUT

Axle Spacer:
 Out _____ mm
 In _____ mm

Ackerman Steer Spacer: _____ mm

4.8mm Ball Stud:
 LA246 (-1mm Low Mount)
 UM129 (Std)

Bump Steer Spacer: _____ mm

Axle Height Spacer:
 Up
 Down

Toe: In Out _____ °

Front Bulkhead Weight Placement:
 None
 Bulkhead Inside _____ oz _____ g
 On the skid plate _____ oz _____ g * 1oz=28g

Sus Mount: UM503 UM567

Caster Spacer:
 25° 0.5
 30° 1.0
 None

Comments: _____

Wheelbase: Long Middle Short

Rear Suspension

Sus Holder Spacer:
 F 0.5 1.0 None
 R 0.5 1.0 None

Anti-Squat: _____ °

Upper Spacer: _____ mm

Wheelbase:
 F: _____ mm
 R: _____ mm

4.8mm Ball Stud:
 UM128 (Std)
 UMW508 (+2mm High Mount)

Body Mount Position:
 High
 Low

Sway Bar: None _____ mm

Camber: _____ °

Rear Hub add Toe:
 0° Type-B (UM519)
 0° Type-B2 (UM519-2)
 0° Alu (UMW516-0)
 0.5° Alu (UMW516-05)
 1° Alu (UMW516-1)

Axle Spacer:
 Out _____ mm
 In _____ mm

Lower Sus Holder:
 Normal Aluminum (Opt)
 Narrow RF UMW511+UMW512
 Wide RF2 UMW514+UMW515

Comments: _____

Diff.
 Gear Diff. # _____
 Ball Diff.

Shock

	Front	Rear
Shock Piston:	_____	_____
Shock Oil:	# _____	# _____
Shock Spring:	_____	_____
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	_____ mm	_____ mm
Shock Top Type:	<input type="checkbox"/> Std:RB5 <input type="checkbox"/> Low:SC	<input type="checkbox"/> Std:RB5 <input type="checkbox"/> Low:SC
5.8mm Ball End:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L

Body / Wing / Chassis

Wing: _____

Body: _____

Lip height: _____


Battery Placement:
 Front Rear

Battery Post:
 Pla Alu

Ride Height: F _____ mm R _____ mm

Weight Placement:

* 1oz=28g



Tire

	Front	Rear
Tire:	_____	_____
Inserts:	_____	_____
Wheel:	_____	_____
Traction Compound:	_____	_____

Comment :

Material

Front Lower Plate: Nomal Hard (UMW522)

Rear Bulkhead: Nomal Hard (UMW506)

Rear Chassis: Nomal Hard (UMW505B)

Servo Saver: Nomal Hard (LA221HB)

Pinion Gear: Steel Aluminium

Shock Ring: O-ring X-ring Red Clear

Electronics

Motor: _____

Pinion/Spur: _____

Battery: _____

ESC: _____

Radio: _____

Servo: _____

Throttle/Brake:
 EPA: _____ Expo: _____

Initial brake: _____

Drag brake: _____

Throttle profile: _____

Steering expo: _____

Steering speed: _____