

Name Shin Adachi Date 29/OCT/2011 Track / City Yatabe Arena Event \_\_\_\_\_

### Front Suspension

**Upper Spacer:** 1 mm

**4.8mm Ball Stud:**  
 UM128(WC Edition)  
 UMW508 (+2mm High Mount)

**Shock Stay:**  
 UM511(RB5)  
 UM525(WC Edition)

**Toe:**  In  Out 0.5 °

**Front Bulkhead Weight Placement:**  
 None  
 Bulkhead Inside \_\_\_\_\_ oz 5 g  
 On the skid plate \_\_\_\_\_ oz 5 g \* 1oz=28g

**Camber:** 1 °

**Axle Type:**  
 UM506(Std/Steel)  
 UM569(WC Edition)

**Ackerman Steer Spacer:** 0 mm

**4.8mm Ball Stud:**  
 LA246(WC Edition)  
 UM129(Std)

**Bump Steer Spacer:** 0 mm

**Axle Spacer:**  
 Out 1 mm  
 In 2 mm

**Axle Height Spacer:**  
 Up  
 Down

**Gaster Spacer:**  
 25°  0.5  
 30°  1.0  
 None

**Wheelbase:**  Long  Middle  Short

Comments: \_\_\_\_\_

### Rear Suspension

**Shock Stay:**  
 UM512(RB5)  
 UMW501  
 UM520(RB5 SP)  
 UM520S(WC Edition)

**Wing Height:**  
 1  
 2  
 3

**Upper Spacer:** 2.5 mm

**Lower Sus Holder:**  
 Normal  RF:RB5  
 Wide  RF2:RB5SP  
 Aluminum(Opt)  UMW511+UMW512  
 UMW514+UMW515

**Sus Holder Spacer:**  
 F  0.5  1.0  
 None

**R  1.0  None**

**Anti-Squat:** 0 °

**Sway Bar:**  None  
 \_\_\_\_\_ mm

**Lower Arm:**  
 UM566(WC Edition)  
 UM521(SP2)

**Upper Spacer:** 2 mm

**Type-B (UM519)**  
**Type-B2 (UM519-2)**

**Wheelbase:**  
 Long  
 Middle  
 Short

**Rear Hub add Toe:**  
 0°Type-B (UM519)  
 0°Type-B2 (UM516-2)  
 0°Alu (UMW516-0)  
 0.5°Alu (UMW516-05)  
 1°Alu (UMW516-1)

**Camber:** 1 °

**Axle Spacer:**  
 Out \_\_\_\_\_ mm  
 In 0.2 mm

**Wheel Shaft Type:**  
 UM522-02(RB5 SP)  
 UM510-02(RB5)

**Swing Shaft:**  
 62.5mm:UM510,UM510-01(RB5)  
 65.5mm:UM522,LA232-01(RB5 SP)

**Wheel Spacer:** 1 mm

Comments: Use NCG sus arm(LAW43)

Comments: Use NCG sus arm(LAW43)

### Shock

	Front	Rear
Shock Piston:	<u>5 Hole</u>	<u>5 Hole</u>
Shock Oil:	# <u>35</u> (TL)	# <u>32.5</u> (TL)
Shock Spring:	<u>Pink</u>	<u>Red</u>
Limiters:	in mm _____ out 0.9mm _____	in mm _____ out 3 mm _____
Shock Length(A):	<u>20</u> mm	<u>29.5</u> mm
Shock Top Type:	<input checked="" type="checkbox"/> Std:RB5 <input type="checkbox"/> Low:ZX5FS	<input checked="" type="checkbox"/> Std:RB5 <input type="checkbox"/> Low:ZX5FS
5.8mm Ball End:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input checked="" type="checkbox"/> L	Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input checked="" type="checkbox"/> L

### Body / Wing / Chassis

**Wing:** Step S **Body:** Bull dog

**Lip height:** 13mm **Battery Placement:**  Front  Rear

**Wing Angle:** 4°  7°  10°  **Battery Post:**  Pla  Alu

**Ride Height:** F 24 mm R 23.5 mm

Weight Placement: \* 1oz=28g

### Tire

	Front	Rear
Tire:	<u>Panther Cry</u>	<u>Panther Cry</u>
Inserts:	<u>Std</u>	<u>Std</u>
Wheel:	<u>Std</u>	<u>Std</u>
Traction Compound:	_____	_____

### Track Condition

- |   |  |
|---|--|
| <input checked="" type="checkbox"/> Smooth        | <input type="checkbox"/> Sandy           |
| <input type="checkbox"/> Bumpy                    | <input type="checkbox"/> Soft Dirt       |
| <input type="checkbox"/> Low Traction             | <input type="checkbox"/> Grass           |
| <input type="checkbox"/> Med. Traction            | <input type="checkbox"/> Blue Groove     |
| <input checked="" type="checkbox"/> Higt Traction | <input checked="" type="checkbox"/> Clay |
| <input type="checkbox"/> Wet                      | <input type="checkbox"/> Dusty           |
| <input type="checkbox"/> Dry                      | <input type="checkbox"/> Other           |

### Kind in spring:

Soft ↑	<u>Pink</u>
	<u>White</u>
	<u>Gold</u>
	<u>Red</u>
	<u>Yellow</u>
	<u>Orange</u>
	<u>Green</u>
↓ Hard	

Comment: \_\_\_\_\_

Throttle profile: P=Punch B=Boost T=Turbo

### Electronics

Motor: Orion VST Pro 7.5T

Pinion/Spur: 22/78

Battery: Orion 90C

ESC: Orion R10 Pro

Radio: Sanwa M11X

Servo: SRG-BLX Type R

Throttle/Brake: \_\_\_\_\_

EPA: 100%/86% Expo: 0%/0%

Initial brake: =Drag

Drag brake: 10%

Throttle profile: P:1 B:0 T:0

Steering expo: 0%

Steering speed: -5%