

ULTIMA RB7 SET UP SHEET



Name _____ Date _____ Truck / City _____ Event _____

Front Suspension

Upper Spacer: _____ mm

4.8mm Ball Stud: Camber: _____ °

UM128(Std.) UMW508 (+2mm High Mount)

AL. Steering Support: None UMW724

4.8mm Ball Stud: LA246 (-1mm Low Mount) 97050M (Std)

Ackerman Steer Spacer: _____ mm

UMW701 Aluminum ST Plate UMW702 Aluminum Clank Arm

Toe: In Out _____ °

Tie Rod: _____

4.8mm Ball Stud Spacer: _____ mm

AXLE SPACER: Out _____ mm In _____ mm

Wheel Hub: UM569 / Std UM506

Wheelbase: F: _____ mm R: _____ mm

Front Bulkhead Weight Placement:

None Bulkhead Inside _____ oz _____ g On the skid plate _____ oz _____ g * 1oz=28g

Caster: 25° 30°

Caster Block: Spacer: 0.5 0° 1.0 2° IN (wide/Std) None 4° OUT (Narrow)

Caster Block Position: _____ mm _____ mm

Bump Steer Spacer: _____ mm

Axle Height Spacer: _____ mm

Knacle: UM763/std. UM714

Comments: _____

Rear Suspension

Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Anti-Squat: _____ °

4.8mm Ball Stud: UM129 UMW508 (+2mm High Mount) 97050M UM128(Std.)

Upper Spacer: _____ mm

Wheelbase: F: _____ mm R: _____ mm

Universal Swing Shaft: _____

Camber: _____ °

Drive Hub : 4mm (TFW113) 4.5mm (LAW30GM/Std.) 5.2mm (UMW523)

Wheelbase: F: _____ mm R: _____ mm

Sway Bar: None _____ mm

Rear Hub Carrier : 0°Type-B (UM519) 0°Type-B2 (UM519-2) 0° Alu (UMW704-0) 0.5°Alu (UMW704-05) 1°Alu (UMW704-1)

Lower Sus. Holder: Plastic RF RF2L RF2 Option UMW511GM (RF/Alu)

Upper Spacer: _____ mm

RR: _____

Mid: _____

Diff.

Gear Diff. # _____ Ball Diff.

Shock

	Front	Rear
Shock Piston:	_____	_____
Shock Oil:	# _____	# _____
Shock Spring:	_____	_____
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	_____ mm	_____ mm
O-ring:	_____	_____
Shock Top type:	<input type="checkbox"/> Alu(UM719/Std) <input type="checkbox"/> UM753-1B	
Ball End type:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	

Battery Placement:

None Screw

Front Rear None

Transmission

Rear Motor Mid-Ship 3 Gear Mid-Ship 4 Gear Mid-Ship Laydown

Chassis

F _____ mm Ride Height: R _____ mm

Battery Type

Straight Separate Short

Type: _____

Truck Condition

Smooth Sandy Bumpy Soft Dirt Low Truction Grass Med. Truction Blue Groove Higt Truction Clay Wet Dusty Dry Other

Wing

UM767/Std. Step 3.0 - Straight Step 3.0 - Round Other _____

_____ mm

Lip: _____ mm

Tire

	Front	Rear	Traction Compound or comment:
Tire:	_____	_____	_____
Inserts:	_____	_____	_____
Wheel:	_____	_____	_____

Other

Motor: _____
ESC: _____
Pinion/Spur: _____

Comment

