

Name: Jason Dias Date: 1/8/2014 Truck / City: OCRC Huntington Beach Event: Club Racing

Front Suspension

Upper Spacer: 1.5 mm

4.8mm Ball Stud: UM128 (Std) UMW508 (+2mm High Mount)

Camber: 1 °

Axle Spacer: Out 1 mm In _____ mm

4.8mm Ball Stud Spacer: 1.5 mm

Wheel Hub: _____ mm

Ackerman Steer Spacer: 0 mm

Bump Steer Spacer: 2 mm

Toe: In Out .5 °

Tie Rod: _____

Front Bulkhead Weight Placement: None Bulkhead Inside _____ oz _____ g On the skid plate _____ oz _____ g * 1oz=28g

Caster: 25° 30°

Spacer: 0.5 1.0 None

Caster Block: 0° 2° 4°

Caster Block position: IN (wide/Std) OUT (Narrow)

Axle Height Spacer: _____ mm 1.5 mm

Comments: Aluminum front axle (UMW507) Wheelbase: F: _____ mm R: 1 mm

Rear Suspension

Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Anti-Squat: _____ °

4.8mm Ball Stud: UM129 UMW508 (+2mm High Mount) 97050M UM128 (Std)

Sway Bar: None _____ mm

Upper Spacer: 3 mm

Wheelbase: F: 2 mm R: 2 mm

RR: RR Mid

Lower Sus Holder: Normal RF Aluminum (Opt) UMW511+UMW512 UMW514+UMW515

Universal Swing Shaft: UM510

Camber: 1 °

Wheelbase: F: 2 mm R: _____ mm

Rear Hub add Toe: 0° Type-B (UM519) 0° Type-B2 (UM519-2) 0° Alu (UMW516-0) 0.5° Alu (UMW516-05) 1° Alu (UMW516-1)

Axle Spacer: Out 1.03 mm In _____ mm

5X10X4 BB in Hub.

Comments: UMW705/707 In-D/In-D Rear wheel spacers .5mm

Motor Position

Rear Motor Midship Motor

Diff.

Gear Diff. # 7000 Ball Diff.

Shock

Shock Piston: W5303-10 1.4x3 Front W5303-09 1.6x2 Rear

Shock Oil: # 27.5 # 25

Shock Spring: White Pink

Limiters: in out mm in out mm

Shock Length (A): _____ mm _____ mm

Shock Length (B): 19.5 mm 27.3 mm

O-ring: ORG03X ORG03X

Ball End type Front: S M L Rear: S M L

Battery Placement:

None Screw

Front Rear

Foam: Front Rear None

Battery Type

Straight Separate Short

Type: Reedy 4100

Chassis

66g brass plate under battery

F: 23 mm Ride Height: R: 22.5 mm

Other

Motor: SchuurSpeed 17.5

ESC: Hobbywing V3.1

Pinion/Spur: 88/42 64P

Tire

Front: AKA Typo Rear: AKA Typo Traction Compound or comment: WD40 15 minutes before race.

Inserts: EVO CC EVO CC Clay compound

Wheel: EVO EVO

Truck Condition

Smooth Sandy Bumpy Soft Dirt Low Traction Grass Med. Traction Blue Groove High Traction Clay Wet Dusty Dry Other

Wing

Blast-S Wing Mount: Blast-L Narrow Step-S Wide Step-M Wing Angle: Step-L Step 2.0 4° 7° 10°

Lip: _____

Comment

Lt. weight body (UMB03LW) / Lt. weight Chassis (UMW720) / Carbon F Tower (UMW714) / F arms (UMW710) / Knuckles (UMW712) / Hub (UMW713) / R Arms (UMW711) / R Tower (UMW716) / Alu Idler (UMW718) / Ti Screws (UMW703)

Motor guard removed / Velvet diff shafts (TFW008) / Chassis Tape (KA40001) / Alu steering set (UMW701/702) / Ceramic Bearings / Battery Servo Taped In + Strapping Tape