

Name: Gabriel "Gabe" Galeano Date: July 2019 Track / City: Gaithersburg, MD. Event: Summer Scorchers

Front Suspension

Upper Spacer: 2 mm

Shock Tower: Std

Toe: In Out 0°

Toe Rod: _____

Front Bulkhead Weight Placement:

None

Bulkhead Inside _____ oz _____ g

On the skid plate _____ oz _____ g (*1oz = 28g)

4.8mm Ball Stud:

UM128 (Std)

UMW508 (+2mm High Mount)

4.8mm Ball Stud Spacer: 1 mm

Caster:

25° 30°

Caster Block:

0.5 0° 1.0 2° None 4°

Spacer:

A (UM502) B (UMW722/Bra) B (UMW723/Alu)

AI Steering Support:

None UMW724

4.8mm Ball Stud:

LA246 (-1mm Low Mount)

97050M (STD)

Ackermann Steer Spacer: 1 mm

UMW701 Aluminum ST Plate

UMW702 Aluminum Crank Arm

Wheel Hub:

UM569/Std

UM506

Wheelbase: F _____ mm R 2 mm

Comments: _____

Rear Suspension

Shock Tower: Std

Anti-Squat: _____°

4.8mm Ball Stud:

UM129

UMW508 (+2mm High Mount)

97050M

UM128 (Std)

Upper Spacer: _____ mm

RR: _____

Mid: _____

Susp Holder Spacer:

F 0.5 1.0 None

R 0.5 1.0 None

Universal Swing Shaft: 65.5

Lower Susp Holder:

Plastic RF RF2L RF2

Option UMW511GM (RF/Alu)

(Opt/Adjustable)

UMW705 (RF/Alu) _____ Block

UMW725 (RF-MID/Bra) _____ B-in Block

(Opt/Adjustable)

UMW706 (RR-RWD) _____ Block

UMW707 (RR-MID) _____ C-in Block

Rear Hub Carrier:

0° Type-B (UM519)

0° Type-B2 (UM519-2)

0° Alu (UMW704-0)

0.5° Alu (UMW704-05)

1° Alu (UMW704-1)

Drive Hub:

4mm (TFW113)

4.5mm (LAW30GM/Std.)

5.2mm (UMW523)

Axle Spacer:

Out _____ mm

In _____ mm

Wheelbase: F _____ mm R 2 mm

Wheelbase: F _____ mm R 0 mm

Comments: _____

Differential:

Gear: _____

Ball: _____

Shocks		Battery placement		Transmission	
Piston:	Front <u>1.6</u> Rear <u>1.7</u>	Back.		<input type="checkbox"/> Rear Motor	
Oil:	# <u>500</u> # <u>400</u>			<input type="checkbox"/> Mid-Ship 3 Gear	
Spring:	<u>Gold</u> <u>Gold</u>			<input type="checkbox"/> Mid-Ship 4 Gear	
Limiters:	In _____ mm In _____ mm			<input checked="" type="checkbox"/> Mid-Ship Laydown	
	Out <u>2 mm</u> Out <u>2 mm</u>				
Length (A):	<u>20.5 mm</u> <u>27.5 mm</u>				
O-Ring:	std std				
Shock Top Type:	<input type="checkbox"/> Alu (UM719/Std) <input type="checkbox"/> UM753-1				
Ball End Type:	Front <input type="checkbox"/> S <input type="checkbox"/> M <input checked="" type="checkbox"/> L				
	Rear <input type="checkbox"/> S <input checked="" type="checkbox"/> M <input type="checkbox"/> L				

Track Condition

- Smooth Sandy
- Bumpy Soft Dirt
- Low Traction Grass
- Med. Traction Blue Groove
- High Traction Clay
- Wet Dusty
- Dry _____

Wing

UM767 (Std)

Step 2.0 - Straight

Step 3.0 - Round

Other _____

Lip: _____ mm

Tire

	Front	Rear
Tire	PL. Positron mc	PL. Positron mc
Insert	PL. Blue	PL. Blue
Wheel	PL.	PL.

Other

Motor: Reds

ESC: Reds T120

Ratio: 21-76

NOTES