

Name _____ Date _____ Track / City _____ Event _____

Front Suspension

Shock Stay:
 UM707(Std.)
 UMW739 Carbon
 UMW744 Wing
 UMW747 Wing Mount

Toe: In Out _____

Tie Rod: _____

Sway Bar: _____ mm

Front Bulkhead Weight Placement:
 None
 Bulkhead Inside _____ oz / g
 On the skid plate _____ oz / g * 1oz=28g

Upper Spacer: _____ mm

4.8mm Ball Stud:
 UM128(Std.)
 UMW508 (+2mm High Mount)

4.8mm Ball Stud Spacer: _____ mm

Caster:
 25°
 30°

Caster Block:
 0.5 0°
 1.0 2° IN (wide/Std)
 None 4° OUT (Narrow)

AL. Steering Support:
 None
 UMW724

Axle Spacer:
 Out _____ mm
 In _____ mm

Wheel Hub:
 UM758(Std.)
 UM506
 UM506

4.8mm Ball Stud:
 LA246 (-1mm Low Mount)
 97050M (Std.)

Ackerman Steer Spacer: _____ mm

UMW701 Aluminum ST Plate
 UMW702 Aluminum Crank Arm

Bump Steer Spacer: _____ mm

Axle Height Spacer:
 _____ mm
 _____ mm

Knuckle:
 UM763(std.)
 UM714

Comments: _____

Wheelbase: F: _____ mm R: _____ mm

Rear Suspension

Shock Stay:
 Std.
 UMW740

Wing Stay:
 1
 2
 3

RR:
 1
 2
 3

Mid:
 1
 2

Sus Holder Spacer:
 F 0.5 1.0 None
 R 0.5 1.0 None

Anti-Squat: _____

Upper Spacer: _____ mm

4.8mm Ball Stud:
 UM129
 UMW508 (+2mm High Mount)
 97050M
 UM128(Std.)

Lower Sus. Holder:
 Plastic
 RF RF2L
 RF2
 Option
 UMW511GM (RF/Alu)

Universal Swing Shaft:
 (Opt/Adjustable)
 UMW705(RF/Alu)
 UMW725(RF-MID/Bra)
 (Opt/Adjustable)
 UMW706(RR-RWD)
 UMW707(RR-MID)

Upper Spacer: _____ mm

Wheelbase:
 F: _____ mm
 R: _____ mm

Wheelbase:
 F: _____ mm
 R: _____ mm

Camber: _____

Sway Bar: _____ mm

Drive Hub:
 4mm (TFW113)
 4.5mm (LAW30GM)
 5.2mm (UMW523)
 6.2mm (UM773/Std.)

Rear Hub Carrier:
 0°Type-B (UM519)
 0°Type-B2 (UM519-2)
 0° Alu (UMW704-0)
 0.5°Alu (UMW704-05)
 1°Alu (UMW704-1)

Sus. Bush:
 In Out / Std.
 Block

Axle Spacer:
 Out _____ mm
 In _____ mm

Diff.:
 Gear Diff. # _____
 Ball Diff. Steel Aluminum

Shock

	Front	Rear
Shock Piston:	_____	_____
Shock Oil:	# _____	# _____
Shock Spring:	_____	_____
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	_____ mm	_____ mm
O-ring:	_____	_____
Shock Top:	<input type="checkbox"/> Alu.(UM719) <input type="checkbox"/> UM753-1B(Std.)	
Ball End:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	
Spring Sheet:	Front: <input type="checkbox"/> Std. <input type="checkbox"/> Low Rear: <input type="checkbox"/> Std. <input type="checkbox"/> Low	

Battery Placement:

Foam:
 Front
 Rear
 None

Transmission

Rear Motor
 Mid-Ship 3 Gear
 Mid-Ship 4 Gear
 Mid-Ship Laydown
 Direct Gear
 Slipper Clutch

Chassis

F _____ mm **Ride Height:** R _____ mm

Battery Type

Straight
 Separate
 Short LCG

Tire

	Front	Rear	Traction Compound or comment:
Tire:	_____	_____	
Inserts:	_____	_____	
Wheel:	_____	_____	

Other

Servo: _____
 Motor: _____
 ESC: _____
 Pinion / Spur: _____

NOTES