

ULTIMA RZ6 SET UP SHEET



Name _____ Date _____ Track / City _____ Event _____

Front Suspension:

Shock Position:

Upper Spacer: _____ mm

4.8mm Ball Stud:
 UM128(Std.)
 UMW508(+2mm High Mount)

4.8mm Ball Stud Spacer: _____ mm

Camber: _____ °
 - +

AL. Steering Support:
 None
 UMW724

4.8mm Ball Stud:
 LA246 (-1mm Low Mount)
 97050M (Std)

Ackerman Steer Spacer: _____ mm

Ackerman arrow direction:
 Front(std) Rear

Option:
 UMW701 Alu ST Plate
 UMW702 Alu Clank Arm

Bump Steer Spacer: _____ mm

Toe: In Out _____ °

Tie Rod: _____

Front Bulkhead Weight Placement:
 None
 Bulkhead Inside _____ 9
 On the skid plate _____ 9

Caster:
 25°
 30°

Spacer:
 0.5
 1.0
 None

Caster Block:
 0°
 2°
 4°

Caster Block Position:
 IN (wide/Std)
 OUT (Narrow)

Wheel Hub:
 UM569 / Std
 UM506

4.8mm Ball Stud: _____ mm

Axle Height Spacer: _____ mm

Wheelbase: F: _____ mm R: _____ mm

Comments: _____

Rear Suspension:

Shock Position:

Wing Stay Position:

Shock Stay Type:
 LA352(std)
 LAW59 (Carbom/2mmLow)

Upper Arm Position:

4.8mm Ball Stud:
 97050M(Std)
 UM129

Upper Spacer: _____ mm

Camber: _____ °
 - +

Sus.Arm:
 LA272(std)
 UM713B

Hub Carrier:
 Type-B (UM519)
 Type-B2 (UM519-2)

0°Type-B(UM519)
 0°Type-B2(UM519-2)
 0°Alu(UMW704-0)
 0.5°Alu(UMW704-05)
 1°Alu(UMW704-1)

Lower Sus Holder Block:
 Front _____ Rear _____

Lower Sus Holder Spacer:
 Front _____ mm Rear _____ mm

Toe In: _____ °

UM713B

Sway Bar:
 None
 _____ mm

Wheelbase: _____ mm _____ mm _____ mm _____ mm

Rear Diff:
 Gear Diff. (Oil:# _____)
 (Oil weight: _____ g)
 Ball Diff.

Comments: _____

Shock:

	Front		Rear	
Shock Piston:	_____	_____	_____	_____
Shock Oil:	# _____	# _____	# _____	# _____
Shock Spring:	_____	_____	_____	_____
Limiters:	in _____ mm	out _____ mm	in _____ mm	out _____ mm
Shock Length(A):	_____ mm	_____ mm	_____ mm	_____ mm
Shock Top Type:	<input type="checkbox"/> Alu(UM719/Std)		<input type="checkbox"/> UM753-1	
5.8mm Ball End:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L		

Chassis:

Ride Height:

Front _____ mm Rear A B _____ mm

Tire: Front _____ Rear _____

Tire: _____

Inserts: _____

Wheel: _____

Traction Compound: _____

Electronics:

Battery:
 Saddle Pack Short

Battery Position:
 Std 8mm Front

Motor Position:
 Front Rear

Motor Mount Position:
 Std 8mm Front

Motor: _____

Pinion/Spur: _____ / _____

Body / Wing:

Body: _____

Wing Mount: Narrow Wide

Wing Dum Height: _____ mm

Wing: _____

Wing Angle: 4° 7° 10°

Lip Height: _____ mm

Material:

Screw: Steel Titanium

Pinion Gear: Steel Aluminium

Shock O-Ring: O-ring X-ring Red Clear

Tire: Front _____ Rear _____

Tire: _____

Inserts: _____

Wheel: _____

Traction Compound: _____

Comment : _____

Track Condition:

<input type="checkbox"/> High Traction	<input type="checkbox"/> Dry	<input type="checkbox"/> Clay
<input type="checkbox"/> Med Traction	<input type="checkbox"/> Dusty	<input type="checkbox"/> Grass
<input type="checkbox"/> Low Traction	<input type="checkbox"/> Sandy	<input type="checkbox"/>
<input type="checkbox"/> Smooth	<input type="checkbox"/> Blue Groove	
<input type="checkbox"/> Bumpy	<input type="checkbox"/> Astroturf	
<input type="checkbox"/> Wet	<input type="checkbox"/> Blue Groove	